Masquerade & Indulgence, The Leather Alternatives

Martin Brattrud's Masquerade and Indulgence Collections offer a compelling, eco-friendly alternative to leather for the contract environment. Beautiful, breathable and highly durable, these faux leathers replicate the rich color and luxurious feel of real leather upholstery. Strong, supple, and stain resistant, they are ideal for high traffic applications. Manufactured free of PVC and plasticizers, Masquerade and Indulgence are responsibly aligned with contract standards for indoor air quality. Made in the USA.

| Masquerade / NY | C Grade: 4 | Indulgence | Grade: 7 | | |
|---------------------------|--|---------------------------|---|--|--|
| Use: | Upholstery | Use: | Upholstery | | |
| Fiber Content: | 100% Nylon | Fiber Content: | 100% Nylon | | |
| Width: | 54 inches | Width: | 54 inches | | |
| Weight: | 16.2 oz / linear yard | Weight: | 16.5 oz / linear yard | | |
| Thickness: | 33 mils | Thickness: | 38 mils | | |
| Abrasian: | 100,000 + double rubs Wyzenbeek Wire Screen (ASTM D-4157-82) | Abrasian: | 100,000 + double rubs Wyzenbeek Wire Screen (ASTM D-4157 – 82) | | |
| Trap Tear Strength: | 30 lbs x 30 lbs (ASTM D-1117-80) | Trap Tear Strength: | 30 lbs x 30 lbs (ASTM D-1117-80) | | |
| Grab Tensile Strength: | 100 lbs x 100 lbs (ASTM D-5034-90) | Grab Tensile Strength: | 100 lbs x 100 lbs (ASTM D-5034-90) | | |
| Crocking: | Wet 5 / Dry 5 (AATCC-8-1988) | Crocking: | Wet 5 / Dry 5 (AATCC-8-1988) | | |
| Colorfastness: | Gas Fumes: (AATCC-23, 3 Cycles); Class 4 – 5 / Little to no color change | Colorfastness: | Gas Fumes: (AATCC-23, 3 Cycles); Class 4-5 / Little to no color change | | |
| Fadeometer Test: | Class 5 / No color change (ATCC-16A-90, 100 hours) | Fadeometer Test: | Class 5 / No color change (ATCC-16A-90, 100 hours) | | |
| Weather-O-Meter: | 225 kj/m ² Little to no color change (Xenon Arc, SAE J-1885) | Weather-O-Meter: | 225 kj/m ² Little to no color change (Xenon Arc, SAE J-1885) | | |
| Sulfide Staining: | No staining (ASTM D-1712-89) | Sulfide Staining: | No staining (ASTM D-1712-89) | | |
| Resistance to Urine: | esistance to Urine: No staining (ASTM D-543) | | No staining (ASTM D-543) | | |
| Flame Resistance: | Passes California 117-2013 and California 117 Section E; Class 1 UFAC/NFPA 260-1989 | Flame Resistance: | Passes California 117-2013 and California 117 Section E; Class 1 UFAC/NFPA 260-1989 | | |
| Custom Color: | Martin Brattrud has the capability of matching a specific color in any Masquerade or Indulgence style. There is a minimum order of 330 yards and no additional costs. Consult your local representative or the factory for more details. | | | | |
| Cleanability Code: | S/W Cleaning instructions are available online at martinbrattrud.com under Leathers & Textiles / Faux Leathers / Technical Data | | | | |

Masquerade & Indulgence, The Leather Alternatives

Martin Brattrud's Masquerade and Indulgence Collections offer a compelling, eco-friendly alternative to leather for the contract environment. Beautiful, breathable and highly durable, these faux leathers replicate the rich color and luxurious feel of real leather upholstery. Strong, supple, and stain resistant, they are ideal for high traffic applications. Manufactured free of PVC and plasticizers, Masquerade and Indulgence are responsibly aligned with contract standards for indoor air quality. Made in the USA.

| Use: | Upholstery When backed, use as Wall Covering | | | | | |
|---|---|-----------------------|-----------------------|--|--|--|
| Fiber Content: | 100% Nylon | Width: | 54 inches | | | |
| Thickness: | 28 mils | Weight: | 13.2 oz / linear yard | | | |
| Abrasian: | 100,000 + double rubs Wyzenbeek Wire Screen (ASTM D – 4157 – 82) | | | | | |
| Trap Tear Strength: | : 30 lbs x 30 lbs (ASTM D-1117-80) | | | | | |
| Grab Tensile Strength: | 100 lbs x 100 lbs (ASTN | D-5034-90) | | | | |
| Crocking: | Wet 5 / Dry 5 (AATCC-8-1988) | | | | | |
| Colorfastness: | Gas Fumes: (AATCC-23, 3 Cycles); Class 4-5 / Little to no color change | | | | | |
| Fadeometer Test: | Class 5 / No color change (ATCC-16A-90, 100 hours) | | | | | |
| Weather-O-Meter: | 225 kj/m² / Little to no c | olor change (Xenon Ar | rc, SAE J-1885) | | | |
| Sulfide Staining: | No staining (ASTM D-17 | 12-89) | | | | |
| Resistance to Urine: | No staining (ASTM D-54 | -3) | | | | |
| lame Resistance: Passes California 117-2013 and Californ Class 1 UFAC/NFPA 260- 1989 | | | Section E; | | | |
| Tunnel Test: | Class A Rated (ASTM E8 | 4) | | | | |
| Custom Color: | Martin Brattrud has the capability of matching a specific color in any Masquerade or Indulgence style. There is a minimum order of 330 yards and no additional costs. Consult your local representative or the factory for more details. | | | | | |
| Cleanability Code: | S/W - Cleaning Instructions are available online under Leathers & Textiles / Faux Leathers / Technical Data on martinbrattrud.com | | | | | |

Masquerade / Pacific, Pacific Pearl, Rockies Grade: 4

Masquerade & Indulgence, The Leather Alternatives

Martin Brattrud's Masquerade and Indulgence Collections offer a compelling, eco-friendly alternative to leather for the contract environment. Beautiful, breathable and highly durable, these faux leathers replicate the rich color and luxurious feel of real leather upholstery. Strong, supple, and stain resistant, they are ideal for high traffic applications. Manufactured free of PVC and plasticizers, Masquerade and Indulgence are responsibly aligned with contract standards for indoor air quality. Made in the USA.

| Masquerade / Ca | rl's Chicago, Sierra | Grade: 4 | Masquerade / Ne | w England | Grade: 4 | |
|---------------------------|--|-----------------|---------------------------|---|----------|--|
| Use: | Upholstery When backed, use a | s Wall Covering | Use: | Upholstery | | |
| Fiber Content: | 100% Nylon | | Fiber Content: | 100% Nylon | | |
| Width | 54 inches | | Width: | 54 inches | | |
| Weight: | 13.2 oz / linear yard | | Weight: | 18.2 oz / linear yard | | |
| Thickness: | 28 mils | | Thickness: | 38 mils | | |
| Abrasian: | 100,000 + double ru Wyzenbeek Wire Scr (ASTM D-4157-82) | | Abrasian: | 100,000 + double rubs Wyzenbeek Wire Screen (ASTM D-4157-82) | | |
| Trap Tear Strength: | 30 lbs x 30 lbs (ASTN | /I D-1117-80) | Trap Tear Strength: | h: 30 lbs x 30 lbs (ASTM D-1117-80) | | |
| Grab Tensile Strength: | 100 lbs x 100 lbs (AS | TM D-5034-90) | Grab Tensile Strength: | 100 lbs x 100 lbs (ASTM D-5034-90) | | |
| Crocking: | Wet 5 / Dry 5 (AATC | C-8-1988) | Crocking: | Wet 5 / Dry 5 (AATCC-8-1988) | | |
| Colorfastness: | Gas Fumes: (AATCC- Class 4-5 / Little to n | | Colorfastness: | Gas Fumes: (AATCC-23, 3 Cycles); Class 4-5 / Little to no color change | | |
| Fadeometer Test: | Class 5 / No color ch (ATCC-16A-90, 100 | | Fadeometer Test: | Class 5 / No color change (ATCC-16A-90, 100 hours) | | |
| Weather-O-Meter: | 225 kj/m² Little to no (Xenon Arc, SAE J-18 | | Weather-O-Meter: | 225 kj/m ² Little to no color change (Xenon Arc, SAE J-1885) | | |
| Sulfide Staining: | No staining (ASTM D | -1712-89) | Sulfide Staining: | No staining (ASTM D-1712-89) | | |
| Resistance to Urine: | No staining (ASTM D | -543) | Resistance to Urine: | Resistance to Urine: No staining (ASTM D-543) | | |
| Flame Resistance: | Passes California 11 California 117 Sectio Class 1 UFAC/NFPA | on E; | Flame Resistance: | Passes California 117-2013 and California 117 Section E; Class 1 UFAC/NFPA 260-1989 | | |
| Tunnel Test: | Class A Rated (ASTM | IE 84) | | | | |
| Custom Color: | Martin Brattrud has the capability of matching a specific color in any Masquerade or Indulgence style. There is a minimum order of 330 yards and no additional costs. Consult your local representative or the factory for more details. | | | | | |
| Cleanability Code: | S/W Cleaning instructions are available online at martinbrattrud.com under Leathers & Textiles / Faux Leathers / Technical Data | | | | | |